



ATTORNEYS AT LAW

FOURTH FLOOR
1755 JEFFERSON DAVIS HIGHWAY
ARLINGTON, VIRGINIA 22202
USA(703) 413-3000
(703) 413-2220 FACSIMILE

OBLONPAT@OBLON.COM

PATENT, TRADEMARK AND COPYRIGHT LAW
AND RELATED FEDERAL AND ITC LITIGATION

WWW.OBLON.COM

FACSIMILE

PLEASE CALL US AT (703) 413-3000 IF THE MESSAGE YOU RECEIVE IS INCOMPLETE OR NOT LEGIBLE

TO	Srilakshmi, Kumar	October 22, 2002
NAME		DATE
	USPTO	703-746-9540
COMPANY/FIRM		FAX #
NUMBER OF PAGES INCLUDING COVER:	4	CONFIRM FAX: <input type="checkbox"/> YES <input type="checkbox"/> NO
FROM	Satheesh Karra	
NAME		OUR REFERENCE
DIRECT PHONE #		YOUR REFERENCE

MESSAGE

Proposed Draft for 09/512,817

Unless otherwise indicated or obvious from the nature of the transmittal, the information contained in this facsimile message is attorney privileged and confidential information intended for the use of the individual or entity named above. If the reader of this message is not the intended recipient or the employee or agent responsible to deliver it to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this communication in error or are not sure whether it is privileged, please immediately notify us by telephone and return the original message to us at the above address via the U.S. Postal Service at our Expense. Thank You.

Dear Examiner Kumar,

Enclosed is a proposed amendment to independent claims 1, 8, 16, and 17. During 10/23 meeting with you, Applicants would like to discuss rejection of independent claims, and distinct dependent claims from each of the claim sets, such as, for example, claims 2-7, and 11 over U.S. Patent No. 5,852,429 to Scheffer et al.

Thank you,

Regards,

Satheesh Karra

703 413 6509

PROPOSED DRAFT for 09/512,817

1. (Amended) In a driving method for a liquid crystal display device, the method comprising:

selecting simultaneously a plurality of lines of row electrode in a liquid crystal display device comprising a plurality of row electrodes and a plurality of column electrodes; and

applying predetermined voltages to the selected lines of the row electrode during a selection period, [the driving method being characterized in that:]

wherein

the selection period of a display frame is divided, and column electrodes are driven with a voltage pattern so as to reduce a change of voltage level in each of the divided periods.

PROPOSED DRAFT for 09/512,817

Page 2 of 3

8. (Amended) In a driving method for a display device having display elements in a matrix form and producing voltage levels for effecting gradation display, the method [for a display device being characterized in that]comprising:

[in a plurality of continuous display frames,] setting a time of at least one frame period [is made]to be different from that of another frame period, in a plurality of continuous display frames;

dividing the selection period of at least one frame in the plurality of display frames [is divided]into divided selection periods[.]; and

providing on-data and off-data [are provided]in the selection period of the non-divided frame period and the divided selection periods to produce a plurality of voltage levels[, and]; wherein

the plurality of voltage levels are used for a display except for the voltage levels in the vicinity of [the]highest [level]and [the]lowest voltage levels.

16. (Amended) In a driving device for a liquid crystal display device for selecting simultaneously a plurality of lines of row electrode in a liquid crystal display device comprising a plurality of row electrodes and a plurality of column electrodes, and applying predetermined voltages to the selected row electrodes during a selection period, the driving device [being characterized by]comprising a driving means for driving column electrodes according to a predetermined voltage

PROPOSED DRAFT for 09/512,817

Page 3 of 3

pattern in each period formed by dividing a selection period of a display frame so that the divided selection periods have a different time ratio.

17. (Amended) In a driving device for a liquid crystal display device for selecting simultaneously a plurality of lines of row electrode in a liquid crystal display device comprising a plurality of row electrodes and a plurality of column electrodes and applying predetermined voltages to the selected row electrodes during a selection period, the driving device[being characterized by comprising]including a driving means, the driving device further comprises:

a timing control means which forms a combination of at least one of two continuous display frames in which time ratio of a display frame period to the other is within 50 – 90%, and supplies a timing signal to column drivers for driving column electrodes,[a timing signal] so that a selection period of at least one of the two continuous display frames is divided into two portions to produce an n (n : an integer of at least 3) number of divided periods,

a gradation processing means for producing n -bit gradation data based on inputted image data to write the n -bit gradation data in frame memories, and

a column data producing means for producing column data by reading sequentially the n -bit gradation data which are stored in the frame memories in the respective divided periods and supplying the produced data to the column drivers.